

STANDARD DEPARTURE -RNAV (GNSS) INSTRUMENT -RWY26

RNAV 1 SID Coding Table of INDUR 4E										
MIN PDG 5.7 % up to FL140										
Navigational performance	Path descriptor	Waypoint identifier	Waypoint coordinates	Fly-Over	True track [°] / Magnetic track [°]	Distance [nm]	Turn direction	Upper limit [ft] / Lower limit [ft]	Speed [kts]	Remarks
RNAV 1	CF	YZ650	400848.4N / 0441829.1E	Y	269.6/ 263	-	-	-	-	-
RNAV 1	TF	INDUR	400656.0N / 0433953.0E	N	266.6 / 260	29.7	-	- / FL140	-	-

RNAV 1 SID Coding Table of EVGED 1E										
MIN PDG 6.8% up to FL140										
Navigational performance	Path descriptor	Waypoint identifier	Waypoint coordinates	Fly-Over	True track [°] / Magnetic track [°]	Distance [nm]	Turn direction	Upper limit [ft] / Lower limit [ft]	Speed [kts]	Remarks
RNAV 1	CF	YZ650	400848.4N / 0441829.1E	Y	269.6/ 263	-	-	-	-	-
RNAV 1	DF	YZ660	401646.8N / 0441422.9E	N	-	-	Right	- / 8000	-	-
RNAV 1	TF	EVGED	402539.3N / 0435901.8E	N	307.2 / 300	14.7	-	- / FL140	-	-

RNAV 1 SID Coding Table of RUDRO 1E										
MIN PDG 7.1% up to FL140										
Navigational performance	Path descriptor	Waypoint identifier	Waypoint coordinates	Fly-Over	True track [°] / Magnetic track [°]	Distance [nm]	Turn direction	Upper limit [ft] / Lower limit [ft]	Speed [kts]	Remarks
RNAV 1	CF	YZ650	400848.4N / 0441829.1E	Y	269.6/ 263	-	-	-	-	-
RNAV 1	DF	YZ660	401646.8N / 0441422.9E	N	-	-	Right	- / 8000	-	-
RNAV 1	TF	RUDRO	403140.6N / 0442359.9E	N	026.2 / 019	16.6	-	- / FL140	-	-

RNAV 1 SID Coding Table of KOSFI 1E										
MIN PDG 6 % up to FL140										
Navigational performance	Path descriptor	Waypoint identifier	Waypoint coordinates	Fly-Over	True track [°] / Magnetic track [°]	Distance [nm]	Turn direction	Upper limit [ft] / Lower limit [ft]	Speed [kts]	Remarks
RNAV 1	CF	YZ650	400848.4N / 0441829.1E	Y	269.6/ 263	-	-	-	220-	-
RNAV 1	DF	YZ670	400512.7N / 0444306.5E	N	-	-	Left	- / 12000	-	-
RNAV 1	TF	KOSFI	400050.0N / 0445855.3E	N	109.7 / 103	12.9	-	- / FL140	-	-